

Model – X-108 HiDuo E-5

Technical Specifications	
- o Lifting Moment of 8.7TM - o Maximum Hydraulic reach 14.2 m - o Maximum Capacity at max reach 450 kg - o Crane Weight of 1843kg	- o Slew Angle of 406° - o Stabiliser Width of 4890mm - o Manually Extending Stabilizers - o 100L Oil Tank – mounted on truck
SPACEvo Control System	6 Function XSDrive2 Remote Control
- o Superb electronic control system packed full of advanced features such as: - o Cabin Protection - o Ballast Optimization (if required) - o Automatic Speed Control - o Automatic Duty Control - o Data Recording and Logging	- o Safe, precise, and superior control of all crane functions - o Ultimate control of all features of the crane at the operators' fingertips - o Electronic Capacity Indicator easily visible for the operator on the remote display - o Supplied with Hip and Shoulder Straps



2-Step Variable Stability Logic (VSL)
The 2-Step VSL system is a proportional stability control system which optimizes the cranes performance based on the stabilizer position. The operator has the option to place the stabilizers at three positions: Max Extension, Mid Extension or Min Extension with the crane automatically calculating the capacity accordingly. The capacity will only be varied where it is required, i.e. only the left-hand side of the crane will be de-rated if the left-hand leg is retracted



