

Model – X-108 HiDuo E-4

| Technical Specifications | |
|---|--|
| <ul style="list-style-type: none"> o Lifting Moment of 9.1TM o Maximum Hydraulic reach 12.0 m o Maximum Capacity at max reach 640 kg o Crane Weight of 1743kg | <ul style="list-style-type: none"> o Slew Angle of 406° o Stabiliser Width of 4890mm o Manually Extending Stabilizers o 100L Oil Tank – mounted on truck |
| SPACEvo Control System | 6 Function XSDrive2 Remote Control |
| <ul style="list-style-type: none"> o Superb electronic control system packed full of advanced features such as: <ul style="list-style-type: none"> o Cabin Protection o Ballast Optimization (if required) o Automatic Speed Control o Automatic Duty Control o Data Recording and Logging | <ul style="list-style-type: none"> o Safe, precise, and superior control of all crane functions o Ultimate control of all features of the crane at the operators' fingertips o Electronic Capacity Indicator easily visible for the operator on the remote display o Supplied with Hip and Shoulder Straps |



| 2-Step Variable Stability Logic (VSL) |
|--|
| <p>The 2-Step VSL system is a proportional stability control system which optimizes the cranes performance based on the stabilizer position. The operator has the option to place the stabilizers at three positions: Max Extension, Mid Extension or Min Extension with the crane automatically calculating the capacity accordingly. The capacity will only be varied where it is required, i.e. only the left-hand side of the crane will be de-rated if the left-hand leg is retracted</p> |



