

## Model – X-082 HiDuo E-4

| Technical Specifications  |  |
|---|--|
| <ul style="list-style-type: none"> <li>o Lifting Moment of 6.6TM</li> <li>o Maximum Hydraulic reach 11.6m</li> <li>o Maximum Capacity at max reach 700kg</li> <li>o Crane Weight of 1403kg</li> </ul>   | <ul style="list-style-type: none"> <li>o Slew Angle of 406°</li> <li>o Stabiliser Width of 4890mm</li> <li>o Manually Extending Stabilizers</li> <li>o 100L Oil Tank – mounted on truck</li> </ul>   |
| <b>SPACEvo Control System</b> <ul style="list-style-type: none"> <li>o Superb electronic control system packed full of advanced features such as: <ul style="list-style-type: none"> <li>o Cabin Protection</li> <li>o Ballast Optimization (if required)</li> <li>o Automatic Speed Control</li> <li>o Automatic Duty Control</li> <li>o Data Recording and Logging</li> </ul> </li> </ul> | <b>6 Function XSDrive2 Remote Control</b> <ul style="list-style-type: none"> <li>o Safe, precise, and superior control of all crane functions</li> <li>o Ultimate control of all features of the crane at the operators' fingertips</li> <li>o Electronic Capacity Indicator easily visible for the operator on the remote display</li> <li>o Supplied with Hip and Shoulder Straps</li> </ul> |



| 2-Step Variable Stability Logic (VSL)  |
|--|
| <p>The 2-Step VSL system is a proportional stability control system which optimizes the cranes performance based on the stabilizer position. The operator has the option to place the stabilizers at three positions: Max Extension, Mid Extension or Min Extension with the crane automatically calculating the capacity accordingly. The capacity will only be varied where it is required, i.e. only the left-hand side of the crane will be de-rated if the left-hand leg is retracted</p> |



