

Model – X-082 HiDuo B-2

Technical Specifications	
<ul style="list-style-type: none"> o Lifting Moment of 7.2TM o Maximum Hydraulic reach 7.2m o Maximum Capacity at max reach 980kg o Crane Weight of 1233kg 	<ul style="list-style-type: none"> o Slew Angle of 406° o Stabiliser Width of 4890mm o Manually Extending Stabilizers o 100L Oil Tank – mounted on truck
SPACEvo Control System	6 Function XSDrive2 Remote Control
<ul style="list-style-type: none"> o Superb electronic control system packed full of advanced features such as: <ul style="list-style-type: none"> o Cabin Protection o Ballast Optimization (if required) o Automatic Speed Control o Automatic Duty Control o Data Recording and Logging 	<ul style="list-style-type: none"> o Safe, precise, and superior control of all crane functions o Ultimate control of all features of the crane at the operators' fingertips o Electronic Capacity Indicator easily visible for the operator on the remote display o Supplied with Hip and Shoulder Straps



2-Step Variable Stability Logic (VSL)
<p>The 2-Step VSL system is a proportional stability control system which optimizes the cranes performance based on the stabilizer position. The operator has the option to place the stabilizers at three positions: Max Extension, Mid Extension or Min Extension with the crane automatically calculating the capacity accordingly. The capacity will only be varied where it is required, i.e. only the left-hand side of the crane will be de-rated if the left-hand leg is retracted</p>



